

**Cilësitë:**

Tipi i bokullës	Bokull për tubat termoplastik (nuk gërrehen)
Materiali	Çelik
Sipërfaqja	E elektro-galvanizuar

Shënim:

Tipi i bokullës zgjidhet në varësi të tubit fleksibël

Kodi	DN	Size	Inches	D1 (mm)	D3 (mm)	LF (mm)
PHY 104	5	3	3/16"	16.0	9.5	28.0
PHY 106	6	4	1/4"	19.0	11.6	29.5
PHY 108	8	5	5/16"	22.0	12.7	29.5
PHY 110	10	6	3/8"	23.0	14.3	32.8
PHY 113	12	8	1/2"	26.0	18.6	34.0
PHY 116	16	10	5/8"	30.0	22.0	36.5
PHY 120	19	12	3/4"	33.0	25.7	41.0
PHY 125	25	16	1"	40.0	31.8	41.0

HANSA FLEX
EMC Engineering Maintenance Center shpk

Në skemat hidraulike vijat interpretohen si më poshtë:

 Linjat e presionit dhe linjat e rikthimit të vajit hidraulik

 Linjat e pilotimit (kontrollit me pilotim)

 Linjat e tubave fleksibël (tubat e gomës)

 Linjat e të lidhura me njëra tjetrën

 Linjat e të PA lidhura me njëra tjetrën

 Linjat ne forme te tille tregojne blloqet hidraulik (Simbolet hidraulike brenda kuadrateve me vije- pike- vije tregojne komponentet hidraulik qe gjendet ne nje bllok hidraulik)